

## CLEAR SEAL

### MATERIAL & FUNCTION

CLEAR SEAL is a water based penetrating sealer suitable for use on sandstone, stone, brick, terracotta or any porous paving masonry surface. CLEAR SEAL has excellent water repellency and will leave a natural finish. It is particularly well suited for use around swimming pools where water marks can be a problem. CLEAR SEAL can also be used as a pre grout seal to aid in clean up. Apply CLEAR SEAL to stone or terracotta tiles prior to grouting to assist in the prevention of grout staining. For single leaf masonry brick walls spray application will reduce or prevent migration of water to inside of the wall.

### APPLICATION

Prior to application of CLEAR SEAL, the surface should be clean and dry. Grease, oil or dirt will interfere with the effectiveness of the sealing or pre-sealing process. Before grouting apply 1 liberal coat of CLEAR SEAL to a clean dry surface by brush, cloth, lambswool applicator or for large areas a broom or cotton mop or spray application may be used. Allow to dry for 6 - 8 hours, (overnight if possible), before grouting. Coverage is typically 12 m<sup>2</sup>/litre, but may vary from 8 m<sup>2</sup>/litre for very porous surfaces or tiles to 16 m<sup>2</sup>/litre for very dense surfaces or tiles.

### SAFETY

Avoid contact with skin & eyes and avoid breathing vapour or spray mist.

### PACKAGING

1 Litre, 5 Litre, 15 Litre & 200 Litre containers

### IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. ALWAYS TEST FIRST.*

Technical Bulletin