

DIAMOND SEAL

Slate & Stone Sealer

MATERIAL & FUNCTION

DIAMOND SEAL is a premium grade acrylic sealer for use in beautifying and protecting slate and stone. DIAMOND SEAL provides a durable finish which highlights and enhances the natural colour and texture while protecting against staining and wear. DIAMOND SEAL can be used in both inside and outdoor areas. DIAMOND SEAL leaves a wet look on the floor and may cause darkening to some surfaces.

APPLICATION

Allow 14 days from laying to ensure the surface is thoroughly dry. The slate surface should have been left absolutely clean during the laying process. Should the slate require cleaning prior to sealing, a further drying period of 2 - 3 days is necessary. **DO NOT USE SPIRITS OF SALTS/HYDROCHLORIC ACID ON SLATE SURFACES.**

Apply one thin coat of DIAMOND SEAL evenly using a brush or lambswool applicator ensuring no bubbles are trapped in the sealer. **DO NOT USE A ROLLER.** Allow to dry overnight. 1 litre of DIAMOND SEAL will cover approximately 10 - 15 sq metres depending on the porosity of slate tiles. It is recommended that 2 coats of DIAMOND SEAL are required for normal domestic use, allowing at least 8 hours between coats and 24 hours before heavy traffic. Depending on the porosity of the slate and the desired level of gloss, additional coats may be applied. (Note: A glossier finish may tend to accentuate scratch marks.) Avoid walking on the floor for 12 hours after final coat. Brushes may be cleaned in SLASOL.

RETREATMENT

Depending on the extent of traffic, your floor will require resealing with DIAMOND SEAL to remove scratching and scuff marks. This will bring your floor back to its original condition. Follow original sealing instructions. If the surface has been previously sealed with a poly-urethane sealer, this must be completely removed using the appropriate paint stripper. Resealing is required after approximately 12 - 24 months inside and 12 monthly outside depending on the amount of wear due to traffic, weathering and cleaning.

CAUTION

This product is highly flammable. Ensure adequate ventilation and no naked flames or smoking. Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

PACKAGING

4 Litre & 20 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product.

*Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***