

HD SEALER

MATERIAL & FUNCTION

HD SEALER is a unique blend of acrylic resins formulated especially for application to all masonry surfaces. HD SEALER highlights the natural colours and texture of the surface and provides protection against wear and staining.

APPLICATION

Ensure the surface is thoroughly dry. The surface should have been left absolutely clean. Should the surface require cleaning prior to sealing, a further drying period of 2 - 3 days should be allowed. Newly laid pavers or stone surfaces should be left to dry for ~14 days prior to sealing. **DO NOT USE SPIRITS OF SALTS/HYDROCHLORIC ACID ON SLATE SURFACES.**

Apply one thin coat of HD SEALER evenly using a brush heavy duty sprayer or lambswool applicator ensuring no bubbles are trapped in the sealer. **DO NOT USE A ROLLER.** Allow to dry overnight. 1 litre of HD SEALER will cover approximately 10 - 15 sq metres depending on the porosity of the surface being treated. At least 2 coats of sealer are recommended for normal domestic use, allow at least up to 8 hours between coats (depending on ambient conditions) and 24 hours before heavy traffic. Depending on the porosity of the surface and the desired level of gloss, additional coats may be applied. (Note: A glossier finish may tend to accentuate scratch marks.) Avoid walking on the floor for 12 hours after final coat. Brushes may be cleaned in CYCLONE.

RETREATMENT

Depending on the extent of traffic, your floor may require resealing with HD SEALER to remove scratching and scuff marks. This will bring your floor back to its original condition. Follow original sealing instructions. If the surface has been previously sealed with a polyurethane sealer, this must be completely removed using the appropriate paint stripper or MULTI STRIP.

Resealing is required after approximately 12 - 24 months inside and 12 monthly outside depending on the amount of wear due to traffic, weathering and cleaning.

CAUTION

This product is highly flammable. Ensure adequate ventilation and no naked flames or smoking. Avoid contact with skin and eyes and avoid breathing vapour or spray mist.

PACKAGING

1, 4, 10, 20, & 200 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***

FATECHBULLMIPA30.doc

Technical Bulletin