

KLEN AQUA BARRIER STONE AND MASONRY SEALER

MATERIAL & FUNCTION

KLEN AQUA BARRIER is a new generation coating style sealer for use on a wide variety of stone and other types of masonry surfaces. KLEN AQUA BARRIER is suitable for both interior and exterior use. KLEN AQUA BARRIER is especially formulated to provide a high degree of resistance to water penetration without the whitening or blanching often observed with other sealers when challenged with continuous water attack.

Klen Aqua Barrier provides stain resistance against the majority of compounds which will stain a floor (including coffee, vegetable oil, wine etc.) whilst giving a satin/low gloss sheen. This makes it ideal for water features where the wet look is desired. KLEN AQUA BARRIER may darken some surfaces and a small test area is recommended.

APPLICATION

- Allow a minimum of 3 days from date of laying/grouting before application of KLEN AQUA BARRIER.
- The surface to be treated should be cleaned and thoroughly dry.
- Apply KLEN AQUA BARRIER using a lambs wool applicator, soft bristle natural or nylon broom or paint brush taking particular care to avoid streaking. Each coat must be a "flow coat" to ensure full saturation of all pores in the stone surface.. A minimum of two even coats should be applied at a direction of 90 degrees to each other. Allow several hours between coats. Applicators may be cleaned using water. Although 2 coats should be sufficient to provide protection to the stone, some very porous stones may require 3 or even 4 coats to ensure complete and long term protection.
- KLEN AQUA BARRIER may also be applied through non-aluminium solvent resistant sprayers.
- Avoid heavy traffic for 24 hours after final coat.
- If in any doubt ring our information hotline for more detailed information

Life expectancy of this sealer is 3 - 5 years dependent on traffic, heavy traffic areas should be resealed as necessary. Surfaces sealed with other products should not be treated with KLEN AQUA BARRIER until suitability and final results are determined, and are in accordance with expectations.

KLEN AQUA BARRIER should cover 8 to 25 m² per litre per coat depending on the porosity of the surface to be treated. 10 m² per litre per coat is the average on most paving products.

Under normal conditions KLEN AQUA BARRIER can remain effective for many years, however, harsh cleaning materials, extreme weathering and strong solvents may have a detrimental effect on the products performance.

PACKAGING

1 Litre, 5 Litre & 15 Litre containers.

IMPORTANT NOTICE TO CUSTOMER

*Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user. **ALWAYS TEST FIRST.***